



LArTPC: From Raw Data to 3D reconstruction


Chao Zhang

Electronic Detector Group, Physics Department

7/8/2022









Liquid Argon Time Projection Chamber (LArTPC)

~mm scale position resolution in 3D




From Bo Yu (BNL)



drift speed 1.6 m / milisec wire pitch 3 mm

Wire-Cell Event Reconstruction

Three time-versus-wire views





Wire-Cell Event Reconstruction




TPC simulation noise filtering signal processing


3D imaging clustering charge-light matching

3D trajectory & dQ/dx fitting cosmic muon tagger multi-track fitting DL-3D vertexing


particle identification





JINST 12 P08003 (2017) JINST 13 P07006 (2018) Brouns Tyles P07007 (2018) Natio JINSTate P01036 (2020)



JINST 13 P05032 (2018) JINST 16 P06043 (2021)







Phys. Rev. Applied 15 064071 (2021) arXiv:2012.07928

JINST 17 P01037 (2022)


Wire-Cell Low Level Signal Processing

- Noise filtering
 - Single-frequency white noise
 - Coherent noise
- □ Signal deconvolution
 - Remove "field response" and "electronic response"

$$M(x',t') = \int_{-\infty}^{\infty} \int_{-x_0}^{x_0} R(x-x',t-t')S(x,t)dxdt$$

Online display:

http://lar.bnl.gov/magnify/



Digital Signal Processing

- ☐ Fundamental theory of linear time-invariant (LTI) system:
 - Any LTI system can be characterized entirely <u>by a single</u> <u>function</u> called the system's <u>impulse response</u>




- y: measured discrete-time signal
- x: the (unknown) true signal
- A:Response matrix

$$x(t) \longrightarrow h(t) \longrightarrow y(t) = h(t) * x(t)$$

$$= \int_{-\infty}^{\infty} h(t - \tau) x(\tau) d\tau$$

Impulse response

Room acoustic response








Image credit: www.prosoundweb.com

h(t)

LArTPC field + electronic response






JINST 13 P07007 (2018)

2D Impulse response

Camera optical response




Hubble telescope impulse response (Image credit: http://web.mit.edu)

h(x, y)

LArTPC 2D response:

y: t * drift velocity

x: wire number * pitch



Change of Basis

Time Domain
$$x(t,w) \rightarrow h(t,w) \rightarrow y(t,w) = h(t,w) * x(t,w)$$


DFT DFT

Frequency $X(f,s) \rightarrow H(f,s) \rightarrow Y(f,s) = H(f,s) \cdot X(f,s)$

Discrete Fourier Transform;


- - Convolution -> multiplication: matrix diagonalization
 - FFT algorithm: $O(N^2) \rightarrow O(N \log N)$: fast computation
 - Frequency-domain filters: reduce noise, regularize fluctuations

Wire-cell Tomographic Reconstruction



□ CAT Scan

- Detector (x-ray generator/receiver) moves across the object (body)
- Axial projections (~180) by detector rotation
- Cross section can be reconstructed at each position along detector movement



■ LArTPC

- Objects (ionizing electrons) move across detectors (wire planes)
- Axial projections (~3) by wire orientation
- Cross section can be reconstructed at each time slice along electron drift

At one time slice


Construct Linear Equations



$$y = Ax$$

$$\begin{pmatrix} u1 \\ u2 \\ v1 \\ v2 \\ v3 \end{pmatrix} = \begin{pmatrix} 0 & 0 & 0 & 1 & 1 & 1 \\ 1 & 1 & 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 1 \\ 0 & 1 & 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & 1 & 0 & 0 \end{pmatrix} \cdot \begin{pmatrix} H1 \\ H2 \\ H3 \\ H4 \\ H5 \\ H6 \end{pmatrix}$$

Use two planes as an illustration



y: measured charge signal on each wire x: the (unknown) true charge deposition in each possible cell

A: bi-adjacency matrix connecting wires and cells (determined solely by wire geometry)

Desired Solution
$$x = \begin{pmatrix} H1 \\ 0 \\ 0 \\ 0 \\ H5 \\ H6 \end{pmatrix}$$


Solve underdetermined linear problem: regularization

- □ Previous example has 6 unknowns, 5 equations: under-determined system
- □ Adding constraints: find the sparsest solution (applies to most physics events): L0-regularization

minimize $||x||_0$, subject to: y = Ax

(L0-norm: number non-zero elements)

NP-hard!



Procedure

- \square Remove unknowns until equations can be solved, then find the best solution with the minimum χ^2
- ☐ a combinatorial problem
 - 2 out of 6: 15 combinations
 - 10 out of 40: 0.8 billion combinations

Compressed Sensing (L1-regularization)


□ Breakthrough: mathematical proof that L0 problem can be well approximated by the L1 problem (Compressed Sensing, Candes, Romberg, and Tao, 2005.)



Emmanuel Candes. (Photo courtesy of Emmanuel Candes.)



Justin Romberg. (Photo courtesy of Justin Romberg.)



Terence Tao. (Photo courtesy of Reed Hutchinson/UCLA.)


https://arxiv.org/abs/math/0503066

minimize $||x||_1$, subject to: y = Ax

(L1-norm: sum of absolute values of the elements)

Or, equivalently, minimize


$$\chi^2 = (y - Ax)^T \cdot V^{-1} \cdot (y - Ax) + \lambda ||x||_1$$




Tomography: reconstruct image with far less projections

Performance in Wire-Cell









☐ Typically, ~tens of seconds to reconstruct the whole 3D image (originally a few hours)

JINST 13, P05032 (2018)



An example MicroBooNE event after 3D reconstruction

Finding Neutrino Interaction




20-30 TPC activities


40-50 PMT activities

- ☐ 3D Cluster based on proximity (kd-tree)
- associate the light flash to the corresponding TPC cluster based on light pattern

3D Pattern Recognition



Math and Machine Learning in LArTPC analysis



Various mathematical and machining learning techniques to further improve the reconstruction and event selection

